

FIBER SC/APC SPLITTERS SERIES





TMT GLOBAL Single mode 19" Rack Mounted Sliding Panel Structure Optical Fiber Splitter s

Features

- Low Insertion loss
- Low PDL
- High Return Loss
- Compact Design
- Wide Operating Wavelength
- Wide Operating Temperature
- High Reliability and Stability
- Uniform Power Splitting

Applications

- Passive Optical Networks (PON)
- Cable Television (CATV Links)
- Local Area Networks (LAN)
- Test Equipment's
- Optical Signal Distribution
- FTTH Deployments (FTTP, FTTH, FTTN, FTTC, FTTB)

OPTICAL PARAMETERS

Parameter	Item		2xN					
			2X2	2X4	2X8	2X12	2X16	2X32
Insertion Loss (23 °C)	Typical	dB	4.3	7.3	10.8	11.9	13.8	16.8
	Max	dB	4.6	7.9	11.3	12.3	14.8	17.8
Channel Uniformity	Typical	dB	0.6	0.8	1.0	1.2	1.5	2.0
	Max	dB	0.8	0.8	1.5	1.8	2.0	2.5
PDL	Typical	dB	0.1	0.1	0.1	0.14	0.2	0.2
	Max	dB	0.2	0.2	0.3	0.3	0.4	0.4
Wavelength dependent loss	Typical	dB	0.1	0.1	0.1	0.1	0.1	0.2
	Max	dB	0.2	0.2	0.3	0.4	0.5	0.5
Temperature stability	Typical	dB	0.3	0.3	0.3	0.3	0.4	0.4
	Max	dB	0.5	0.5	0.5	0.5	0.5	0.5
Operating Wavelength	nm		1260 ~ 1650					
Return Loss	Min.	dB	50					
Directivity	Min.	dB	55					
Operating Temperature	°C		-40 ~ 85					
Storage Temperature	°C		-40 ~ 85					
Fiber Length			1.0+/0.1 or Customer specified					
Fiber Type			ITU G.652D,G.657A1/A2,					
Connector Type			SC/APC			LC/APC		

Model No	Product ID	Ordering Information
TMT-3335	TMT-Y121SSL	2X12 SC/APC SM RACK MOUNT SPLITTER