

DATA PATCH PANEL SERIES



DATA PATCH PANEL SERIES



PATCH PANEL SERIES



12/24 PORT CAT6/CAT6A PATCH PANEL

FEATURES

- Exceptional material properties and design
- Integrated full installation accessories (supplied free of charge), including labels and icons, clip organizers and T-raps- providing a simple and elegant cable termination and identification.
- Optional plastic front panels
- Exceeding Category 6 performance - providing full support to Gigabit Ethernet over Category 5e and Category 6 cabling systems.
- High quality metal casing
- Compatible with 24-22 AWG solid conductors
- Available in T568A, T568B or Universal pin/pair assignment

PHYSICAL AND MECHANICAL PROPERTIES

| Type | CAT6 UTP | CAT6A FTP |
|-----------------------------|--|--|
| Wire size range | 22 to 26 AWG, Solid or stranded Cables | 22 to 26 AWG, Solid or stranded Cables |
| Material of construction | Galvanized Steel | SPCC |
| Standard Color | Black/Grey | Black/Grey |
| Connector module holder | High impact, Flame-retardant plastic compound, UL 94 V-0 | High impact, Flame-retardant plastic compound, UL 94 V-0 |
| Housing material | High impact, Flame-retardant plastic compound, UL 94 V-0 | High impact, Flame-retardant plastic compound, UL 94 V-0 |
| Storage temperature range | -20 to +80C | -20 to +80C |
| Temperature operating range | -40 to +60C | -40 to +60C |
| Packaging | One unit per box | One unit per box |

Ordering Information

| Model No | Product ID | Description |
|----------|------------|-----------------------------------|
| TMT-4352 | TMT-0212U | 12PORT CAT6 UNLOADED PATCH PANEL |
| TMT-4364 | TMT-0224U | 24PORT CAT6 UNLOADED PATCH PANEL |
| TMT-4374 | TMT-0324U | 24PORT CAT6A UNLOADED PATCH PANEL |

