

# 64CH STAND ALONE NVR





## TMT Global 64ch NVR Series With Embedded Linux Full HD Network Backup USB Hard Disk 4K/8MP 2U 9HDD H.265 NVR

### Feature:

- H.265 64CH 4K/8MP 2U 9 HDD NVR
- Support TMTEYE P2P cloud services
- Provide networked centralized monitoring and management software
- Support H.265+/H.265/H.264 coding front end adaptive access
- Support ONVIF, High profile S and High profile G

### Product highlights

- Supports 16HDD, supports hard disk hot swap, and supports RAID5.
- Support Slink super protocol, plug and play. Subverting tradition, IPC does not require IP
- Connect to network cameras that comply with ONVIF, RTSP standards and many mainstream manufacturers
- Supports ONVIF external channel and can directly interface with international standard ONVIF protocol platform.
- Support GB28181 standard communication protocol
- Support preview, storage and playback of 4K HD network video
- Support H.265, H.264 encoding front-end adaptive access
- New UI operation interface, support one-click to open recording function
- Support IPC centralized management, including IPC parameter configuration, information import/export, voice intercom and upgrade, etc.
- Support double password verification playback and backup
- Supports instant playback under the preview screen without affecting other channel previews
- Supports up to 16 channels of 1080p synchronous playback and multi-channel synchronous playback
- Support image multi-channel playback and support thumbnail playback
- Supports ultra-high speed playback of 4,8,16,32, 64, etc.

### Specification

Operating System	Embedded LINUX operating system			
Video Standard	H.265+/ H.265/H.264			
Intelligent Support	NVR support	The first 8 channels; with any ONVIF protocol IPC : Target count, object left/lost, area detection, line crossing		
	IPC support	Full channel ; with same brand <b>TMT Global</b> Smart IPC : Target count, object left/lost, area detection, line crossing ; Full channel ; with same brand <b>TMT Global</b> Smart IPC : Target count, object left/lost, area detection, line crossing · audible alarm, license plate detection, face detection, fire detection, video diagnosis, scene change		
Video & Audio Input	Video Input	64ch 4K and below resolution H.265+/H.265/H.264 IP camera		
	Bandwidth	512MB	Audio Input	IPC composite stream network audio input
Video & Audio Output	VGA Output	1ch	HDMI Output	1ch ; HDMI can output audio at the same time
	Video Resolution	4K and below resolution	Video Format	H.265/H.264 / MJPEG
External Port	Internet Port	2 x 10M/100M/1000M adaptive Ethernet port	USB Port	1x USB3.0 · 2x USB 2.0
	Serial Port	RS-485	Alarm Input	4ch
HDD	Alarm Output	4ch		
	HDD Port	9x SATA+1x ESATA HDD Port	MAX Capacity	Each port up to 8TB
Network Management	Network Protocol	UPnP (Plug & Play), SNMP (Simple Network Management), NTP (Network Timekeeping), SADP (Device Network Search), SMTP (Mail Service), NFS (Access NAS), iSCSI (IP SAN Application), PPPoE (Dial-up Internet access), DHCP (automatically obtain IP address)		
P2P Remote	<b>TMTEYE</b>	Supports iPhone, iPad, Android Smart phone		
Outside Carton	2 pcs/carton. Dimension : 555mm×545mm×470mm ; Packing : 21Kg			
Power Supply	ATX110-220V 250W 50-60Hz			
Working Temperature	-10 °C -- + 55 °C			
Working Humidity	10%-90%			
Power Consumption (no HDD)	≤30W (without HDD)			
Dimensions	Device : 440mm×432mm×90mm, Packing : 539mm×550mm×225mm			
Weight (Without HDD)	N.W. : 7.4Kg ; Packing : 9.8Kg			

### Ordering Information

Model	Product code	Description
<b>TMT-4964</b>	TMT-SN64298	64CH STAND ALONE NVR