

DATA PATCH CORD SERIES



DATA PATCH CORD SERIES



www.tmtglobal.co.uk info@tmtglobal.co.uk

Head Office 120 Baker Street, 3rd Floor, London, England, W1U 6tU,
United Kingdom



DATA PATCH CORD SERIES



CAT6A STP PATCH CORD

TMT Global Category 6a STP patch cord are manufactured tested and complied with IEC 60332-1-2 EN 50173-1:2011 ISO/IEC11801:2011(Ed. 2.2) ANSI/TIA/EIA-568.2-D IEC61935-2:2010(Ed.3.0) EN 50173-2:2007 including amendment A1:2010 requirements for patch cord assemblies and provide high performance levels for structured cabling systems.

APPLICATION

10BASE-T, 100BASE-TX Fast Ethernet,
1000BASE-T (IEEE802.3)
100VG-AnyLAN (IEEE802.12)
550 MHz Broadband Video
Voice, T1, ISDN
155/ 622 Mbps ATM
Power over Ethernet (POE)

GENERAL SPECIFICATION

4 Pairs shielded Twisted Pair (STP) Cable
Gold Plated: 30U"
Color Code: Aqua/Black/Blue/green/Grey/Orange/Red/Violet/White/Yellow r custom color
Length : 0.12/0.15/0.50/1/2/3/5/8/10/15/20/25/30/40/50/70/100/meter r custom Length
Contact blade: Phosphor Bronze
Insulation Material: HD-PE-PVC-LSZH
Jacket Material: PVC UL94V-0

PHYSICAL AND MECHANICAL PROPERTIES

Conductor Resistance: $\leq 5\Omega - \leq 20\Omega$
Insulation Resistance: $\geq 10M\Omega$
Characteristic Impedance: 100 — 6 Ohm @ 1-250MHz -1-500 MHZ
Contact Resistance: 20 m Ohm max
Resistance unbalance: 2% max
Dielectric strength: 1000 volts/1 minute min rms
Cable to Plug Tensile Strength: 9 Kgf (90N) min
Durability: 750
Temperature Operating Range: -25°C to 70°C
Country Of Origin: Made in UAE

